

GENERATOR CHARACTERISTICS

PRIME

STANDBY

Power	kVA	1150	1250
Power	kW	900	1000
Standart Voltage	V	400/230	400/230
Revolution Per Minute	r.p.m	1500	1500
Rated At Power Factor	Cos Phi	0,8	0,8

STANDBY POWER

Supplying of electrical power at variable load, in the event of normal utility power failure according to ISO85281.

This rating is maximum power, no overload capability is available.

PRIME POWER

Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility powerfailure according to ISO85281. 10% over load capability is available.



STANDART FEATURES

- 4 stroke 1500RPM, water cooled heavy duty diesel engine
- Dry type replacable air filter
- Heatresistant radiator for 50 °C
- Flexible oil pipes and oil draining valve
- Preheater 4 poles synchrontype, single bearing, brushless alternator
- Electrical wiring diagram User manual and operating manual
- Fuel tank housed in the chassis Industrial type silencer
- Electrostatic paint coated, steel, welded chassis
- Electronic battery charger
- Batteries and cables
- Protection system on manual run
- Lubrication oil and anti – freeze
- Soundproof canopy
- Circuit Breaker - Electronic ABB

ENGINE CHARACTERISTICS

Manufacturer	Cummins
Model	KTA38-G9
Type	4 Stroke, 60° Vee
Stand-by Power	<i>kW/m</i> 1090kw /1460HP
Prime Power	<i>kW/m</i> - /-
No. of cylinder	12
Displacement	<i>lt</i> 38
Cooling System	Water Cooling
Bore x Stroke	<i>mm</i> 159x159
Compression Ratio	14.5:1
Aspiration	Turbocharged
Induction system	Electronic

ELECTRICAL SYSTEM

Electrical System	<i>VDC</i>	12
Starter		DC24V
Charge Alternator Current	<i>A</i>	35

COOLING SYSTEM

Coolant Capacity Standard	<i>lt</i>	133.5
Thermostat Coolant Alarm	<i>°C</i>	82-93
Temperatur	<i>°C</i>	96.1

FUEL SYSTEM

Lubricant Oil Capacity	<i>lt</i>	35,7
Fuel Consumption Under 100% Load	<i>lt/h</i>	N / A L/h
Fuel Consumption Under 75% Load	<i>lt/h</i>	N / A L/h
Fuel Consumption Under 50% Load	<i>lt/h</i>	N / A L/h

EXHAUST SYSTEM


Max. Allowable Back Pressure		10kPa
Standard Exhaust	<i>mm</i>	152

ALTERNATOR CHARACTERISTICS

Manufacturer	Leroy Somer
No Of Phases	3
Power Factor	0,8
No Of Bearings	Single
No Of Poles	4
No Of Leads	6-12
Insulation Class	H
Degree Of Protection	IP23
Excitation System	AVR


CONTROL PANEL FEATURES

- Deepsea 7320
- Diesel and gas genset support
- 400Hz operation support
- 400 event logs full snapshot
- Multiple Automatic test program
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V&I
- Harmonic analysis of V&I
- Synchroscope & check synch 16Amp
- MCB & GCB outputs 8 configurable digital outputs
- Outputs expandable to 40 4 configurable analog outputs
- Battery charge run enabled
- Weekly Operation Schedule
- Dual mutual standby with equal aging of gensets
- Manual speed fine adjust some ECU's
- Automatic fuel pump control
- Disable protection feature
- Excess protection power
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Waveform display of V&I
- Battery backup real time clock Idle speed control
- All parameters front panel editable
- Multiple nominal conditions
- Contactor & MCB drive
- 4 quadrant genset power counters
- Mains power counters
- Fuel filling counter
- Fuel consumption counter
- Free configuration software
- Allow SMS controls
- Mobile genset support
- Automatic GSM geolocation
- GPS connectivity (USB & RS232)
- Modem & ethernet diagnostic
- Configurable through USB, RS485,
- Ethernet and GPRS
- Ready for central monitoring Ethernet and GPRS



OPEN TYPE DIMENSIONS

Length	mm	4600
Width	mm	2140
Height	mm	2520
Weight	kg	7600



CANOPIED TYPE DIMENSIONS

Length	mm	5900
Width	mm	2280
Height	mm	2550
Weight	kg	11750
Base fuel tank volume (L)	l	660

